

## WFI Samplers

### Sample Lines for WFI Sampling

**Ideal for:** Sampling any Bioprocess water drop, where sterility is important.

WFI Samplers are the only single use sampler that uses our proprietary SterilEnz®-II/AT Polypropylene Sanitary fittings that are equipped with a pre-attached medical grade silicone gasket. This feature prevents operators from misaligning or dropping gaskets during connection to the WFI Water drops.



✓ **Validation:** WFI Samplers are intended for single-use and are discarded after each sample. Therefore, cleaning validation & potential cross contamination issues are eliminated.

✓ **Convenience:** The built-in gasket saves time, money & eliminates gasket preparation by the end-user. Easy hold tab on the fitting for easy on/off installation.

✓ **Handling:** Our gaskets cannot be miss-aligned or dropped by operators during assembly. This feature eliminates leaks and potential safety risks when sampling HOT WFI Drops.

✓ **Quality & Integrity by Design:** All components are USP Class VI Compliant and ADCF (animal derived component free).

Part Number	Description	Quantity
TS4-1200-AT-018	WFI Sampler, 1/4" ID x 7/16" OD silicone tube, SterilEnz®-II/AT mini-TC Flange, irradiated, 18" Length	10/pack
TS4-1200-AT-036	WFI Sampler, 1/4" ID x 7/16" OD silicone tube, SterilEnz®-II/AT mini-TC Flange, irradiated, 36" Length	10/pack
TS4-1600-AT-018	WFI Sampler, 1/4" ID x 7/16" OD silicone tube, SterilEnz®-II/AT 1"/1.5"-TC Flange, irradiated, 18" Length	10/pack
TS4-1600-AT-036	WFI Sampler, 1/4" ID x 7/16" OD silicone tube, SterilEnz®-II/AT 1"/1.5"-TC Flange, irradiated, 36" Length	10/pack